

XF PREMIUM ENGINE OIL 5W30 ECO

Page: 1 Compilation date: 13/07/2010 Revision date: 19/11/2020 Revision No: 1d

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name:	XF PREMIUM ENGINE OIL 5W30 ECO
Product code:	6221
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Use of substance / mixture:	Engine oil
1.3. Details of the supplier of	the safety data sheet
Company name:	Millers Oils Ltd
	Hillside Oilworks
	Rastrick Common
	Brighouse
	West Yorkshire
	HD6 3DP
	United Kingdom
Tel:	+44 (0)1484 713201
Fax:	+44 (0)1484 721263

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Email: h.s@millersoils.co.uk

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

XF PREMIUM ENGINE OIL 5W30 ECO

3.2. Mixtures

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC - REACH registered number(s): 01-2119484627-25-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-157-1	64742-54-7	-	Asp. Tox. 1: H304	70-90%

C14-16-18 ALKYL PHENOL - REACH registered number(s): 01-2119498288-19-XXXX

-	-	-	Skin Sens. 1B: H317; STOT RE 2:	<1%
			H373	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

XF PREMIUM ENGINE OIL 5W30 ECO

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leakside up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	5.4 mg/m3	Workers	Local
DNEL	Inhalation	1.2 mg/m3	Consumers	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Nitrile gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

XF PREMIUM ENGINE OIL 5W30 ECO

Page: 4

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties			
State:	Liquid		
	Pale brown		
Odour:	Barely perceptible odour		
Evaporation rate:			
-	Non-oxidising (by EC criteria)		
Solubility in water:			
-	Most organic solvents.		
	No data available.		
Kinematic viscosity:			
Viscosity test method:	Kinematic viscosity in 10-6 m2/s at 40°C ((ISO 3219)	
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:		upper:	No data available.
Flash point°C:	>200 Pa	art.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:			No data available.
VOC g/l:	No data available.		
-			

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

XF PREMIUM ENGINE OIL 5W30 ECO

Page: 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

- **NB:** The user's attention is drawn to the possible existence of regional or national
 - regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

XF PREMIUM ENGINE OIL 5W30 ECO

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
Phrases used in s.2 and s.3:	H304: May be fatal if swallowed and enters airways.
	H317: May cause an allergic skin reaction.
	H373: May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.